

PRACTICAL

RUGGED

SMART

Thermoreactor

LABQUEST
BY BOROSIL®



DYNAMIC



SAFE



SIMPLE

Compact & Convenient

Thermoreactor



- Compact design reduces bench space.
- Digestion in vials additionally saves on reagents.



- Unique one key operation allow ease and convenience of use and convenience of use.
- Versatility of the product comes from extended applications in determination of COD, Trace metals, TOC, Total Phosphate, Total Nitrogen, Total Chrome



- Transparent UV protective lid helps visual monitoring of process.
- Ensues additional safety during operation.
- Corrosion resistant housing for longer heater life of the unit

| Model | |
|----------------------------------|--|
| Parameters/ Model No. | COD120 |
| Reflux Type | Sealing |
| Positions | 12 Position |
| Capacity | 16mmX100mm vials |
| Heating Block | Aluminium |
| Temperature Range | Ambient to 180°C |
| Presets | at 100°C, 120°C & 150°C with optional time of 30, 60, 90, 120 mins |
| Temperature Accuracy | ±1°C |
| Display | LED |
| Process Timer | 0-999 min |
| Temperature Control | Yes with Set value and Present value |
| Time Control | Yes with Set value and Present value |
| Transparent Lid | UV protection |
| Power consumptions | 200 W |
| Current Consumption | 1.5 A |
| Unit External Dimensions (WxDxH) | (275X185X150) mm |
| Ordering Code | BLFACOD12000000000 |

Unit to be supplied with 12nos. of digestion vials

BOROSIL®
Scientific

1101, Crescenzo, G-Block, Opp. MCA Club,
Bandra Kurla Complex, Bandra (E), Mumbai - 400 051, India
T : +91 22 6740 6300 F : +91 22 6740 6514
E : borosil@borosil.com W : www.borosil.com

Manufactured by :
BOROSIL TECHNOLOGIES LTD.
21-24, Plot No. 8, Indialand Global Industrial Park,
Hinjewadi Phase - 1, Pune - 411 057